

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

- **Product identifier**
- **Trade name: Surf-Kote M-2049**
- **Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
HOHMAN PLATING & MFG.
814 Hillrose Avenue
Dayton, Ohio 45404-1132
(937) 228-2191
- **Emergency telephone number:**
Chemtrec (US): (800) 424-9300
Chemtrec (Outside US): (703) 527-3887 (Collect calls accepted)

Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Care. 2 H351 Suspected of causing cancer.
Repr. 1A H360 May damage fertility or the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tax. 1 H304 May be fatal if swallowed and enters airways.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tax. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Label elements**GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049**Hazard pictograms**

GHS02 GHS07 GHS08 GHS09

Signal word Danger**Hazard-determining components of labeling:**Molybdenum Disulphide
Toluene
Methyl isobutyl ketone
trilead bis(orthophosphate)
Antimony trioxide**Hazard statements**Flammable liquid and vapor.
Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
May damage fertility or the unborn child.
May cause respiratory irritation. May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Toxic to aquatic life with long lasting effects.**Precautionary statements**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dust/fume/gas/mist/vapors/spray.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.
Wear protective gloves.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Avoid release to the environment.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
If swallowed: Immediately call a poison center/doctor.
IF **ON SKIN** (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
IF **INHALED**: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a poison center/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Get medical advice/attention if you feel unwell.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

- Do NOT induce vomiting.
- In case of fire: Use for extinction: CO2, powder or water spray.
- If on skin: Wash with plenty of water.
- Collect spillage.
- Take off contaminated clothing and wash it before reuse.
- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

Unknown acute toxicity:

16 percent of the mixture consists of ingredient(s) of unknown toxicity.

Classification system:

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



Hazard(s) not otherwise classified (HNOC): None known

Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous Components:

| | | |
|-------------------------------------|---|--------|
| CAS: 108-88-3 RTECS: XS 5250000 | Toluene Flam. Liq. 2, H225; Repr. 2, H361; STOT RE 2, H373; Asp. Tax. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336 | 15-35% |
| CAS: 1317-33-5 RTECS: QA 4697000 | Molybdenum Disulphide Acute Tax. 4, H332 | 15-35% |
| CAS: 108-10-1 RTECS: SA 9275000 | Methyl isobutyl ketone Flam. Liq. 2, H225; Care. 2, H351; Acute Tax. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335 | 15-35% |
| CAS: 78-93-3 RTECS: EL 6475000 | Methyl ethyl ketone Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336 | 15-35% |
| CAS: 28470-78-2 | Formaldehyde Polymer with 3-Chloro-1-Propene & Phenol Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320 Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320 | 15-35% |
| CAS: 1309-64-4 | Antimony trioxide Care. 2, H351 | 2-12% |
| CAS: 7446-27-7 | trilead bis(orthophosphate) Care. 2, H351; Repr. 1A, H360; STOT RE 2, H373; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | 2-12% |
| CAS: 71-36-3 RTECS: EO 1400000 | Butanol Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tax. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 | 2.5% |

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049**Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness, place patient securely on side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation occurs, consult a doctor.

After eye contact:

Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If swallowed and symptoms occur, consult a doctor.**Information for doctor:****Most important symptoms and effects, both acute and delayed:** No further relevant information available.**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

Extinguishing media**Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.**For safety reasons unsuitable extinguishing agents:** Water with full jet**Special hazards arising from the substance or mixture** No further relevant information available.**Advice for firefighters****Protective equipment:**

Mouth respiratory protective device.

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the collected material according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep protective respiratory device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with occupational exposure limits:**

108-88-3 Toluene

| | |
|-----|---|
| PEL | Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift |
| REL | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV | Long-term value: 75 mg/m ³ , 20 ppm BEi |

1317-33-5 Molybdenum Disulphide

| | |
|-----|---|
| PEL | Long-term value: 15* mg/m ³ *Total dust |
| TLV | Long-term value: 10* 3** mg/m ³ as Mo; *inhalable fraction ** respirable fraction |

108-10-1 Methyl isobutyl ketone

| | |
|-----|---|
| PEL | Long-term value: 410 mg/m ³ , 100 ppm |
| REL | Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm |
| TLV | Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEi |

78-93-3 Methyl ethyl ketone

| | |
|-----|--|
| PEL | Long-term value: 590 mg/m ³ , 200 ppm |
|-----|--|

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

| | |
|-----|--|
| REL | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm |
| TLV | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEi |

1309-64-4 Antimony trioxide

| | |
|-----|--|
| PEL | Long-term value: 0.5 mg/m ³ |
| REL | Long-term value: 0.5 mg/m ³ as Sb |
| TLV | Long-term value: 0.5 mg/m ³ as Sb; Production: L |

7446-27-7 trilead bis(orthophosphate)

| | |
|-----|--|
| PEL | Long-term value: 0.05* mg/m ³ *see 29 CFR 1910.1025 |
| REL | Long-term value: 0.05* mg/m ³ *8-hr TWA, See Pocket Guide App. C |
| TLV | Long-term value: 0.05 mg/m ³ BEi |

71-36-3 Butanol

| | |
|-----|---|
| PEL | Long-term value: 300 mg/m ³ , 100 ppm |
| REL | Ceiling limit value: 150 mg/m ³ , 50 ppm Skin |
| TLV | Long-term value: 61 mg/m ³ , 20 ppm |

Ingredients with biological limit values:

108-88-3 Toluene

| | |
|-----|---|
| BEi | 0.02 mg/L blood prior to last shift of workweek Toluene |
| | 0.03 mg/L urine end of shift Toluene |
| | 0.3 mg/g creatinine urine end of shift o-Cresol with hydrolysis (background) |

108-10-1 Methyl isobutyl ketone

| | |
|-----|---|
| BEi | 1 mg/L urine end of shift MIBK |
|-----|---|

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049**78-93-3 Methyl ethyl ketone**BEi 2 mg/L
urine
end of shift
MEK

· **Additional information:** The lists that were valid during the creation of this SOS were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

· **Eye protection:**



Tightly sealed goggles

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Liquid

· **Color:**

Bluish black

· **Odor:**

Organic solvent

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

- **Change in condition**
 - Melting point/Melting range:** Not determined.
 - Boiling point/Boiling range:** 76 °C (169 °F)
- **Flash point:** 23 °C (73 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 460 °C (860 °F)
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- **Explosion limits:**
 - Lower:** 1.2 Vol%
 - Upper:** 11.5 Vol%
- **Vapor pressure @ 20 °C (68 °F):** 95 hPa (71 mm Hg)
- **Density@ 20 °C (68 °F):** 1.2 g/cm³ (10.014 lbs/gal)
- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in I Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 54.0%
 - VOE content:** 54.0%
- **Other information** No further relevant information available.

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition I conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, flame and ignition sources.
- **Incompatible materials:** Strong oxidizing agents.
- **Hazardous decomposition products:**
 - Lead oxide vapor
 - Oxides of carbon (COx)

(Contd. on page 9)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

· **Information on toxicological effects**

· **Acute toxicity:**

· **LDILC50 values that are relevant for classification:**

108-88-3 Toluene

| | | |
|------------|----------|----------------------|
| Oral | LD50 | 5000 mg/kg (rat) |
| Dermal | LD50 | 12124 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 12.5-28.8 mg/l (rat) |

1317-33-5 Molybdenum Disulphide

| | | |
|------------|----------|------------------|
| Inhalative | LC50/4 h | 12.82 mg/l (rat) |
|------------|----------|------------------|

108-10-1 Methyl isobutyl ketone

| | | |
|------------|----------|---------------------|
| Oral | LD50 | 2080 mg/kg (rat) |
| Dermal | LD50 | 16000 mg/kg (rab) |
| Inhalative | LC50/4 h | 8.3-16.6 mg/l (rat) |

78-93-3 Methyl ethyl ketone

| | | |
|------------|---------------|-----------------------------|
| Oral | LD50 | 3300 mg/kg (rat) |
| Dermal | LD50 | 5000 mg/kg (rabbit) |
| Inhalative | LC50/96 hours | 3130-3320 mg/l (Pimephales) |

1309-64-4 Antimony trioxide

| | | |
|------|------|--------------------|
| Oral | LD50 | >20000 mg/kg (rat) |
|------|------|--------------------|

71-36-3 Butanol

| | | |
|------------|---------------|----------------------------|
| Oral | LD50 | 790 mg/kg (rat) |
| Dermal | LD50 | 3400 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 8000 mg/l (rat) |
| | LC50/96 hours | 1376 mg/l (Fathead Minnow) |
| | LC50/48 hrs | 1328 mg/l (Water flea) |

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:**

Irritating effect.

Causes serious eye irritation.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· **Carcinogenic categories**

· **/ARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

| | |
|--|----|
| 108-10-1 Methyl isobutyl ketone | 2B |
| 1309-64-4 Antimony trioxide | 2B |
| 7446-27-7 trilead bis(orthophosphate) | 2B |
| · NTP (National Toxicology Program) | |
| 7446-27-7 trilead bis(orthophosphate) | R |
| · OSHA-Ca (Occupational Safety & Health Administration) | |
| None of the ingredients are listed. | |

· Toxicity

· Aquatic toxicity:

Avoid release into the environment. Runoff from fire control or dilution water may cause pollution.

108-88-3 Toluene

EC50 10 mg/l (Green algae)

8.0 mg/l (Water flea)

78-93-3 Methyl ethyl ketone

EC50 | 7060 mg/l (daphnia)

· Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· Ecotoxicological effects:

· Remark: Toxic for fish

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

· Waste treatment methods

· Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

· UN-Number

· DOT, ADR, IMDG, IATA

UN1992

(Contd. on page 11)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

· **UN proper shipping name**

· **DOT**

Flammable liquids, toxic, n.o.s. (Ethyl methyl ketone, Antimony trioxide)

· **ADR**

UN1992 Flammable liquids, toxic, n.o.s. (Ethyl methyl ketone, Antimony trioxide), ENVIRONMENTALLY HAZARDOUS

· **IMDG**

FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL METHYL KETONE (METHYL ETHYL KETONE), Antimony trioxide), MARINE POLLUTANT

· **IATA**

FLAMMABLE LIQUID, TOXIC, N.O.S. (ETHYL METHYL KETONE (METHYL ETHYL KETONE), Antimony trioxide)

· **Transport hazard class(es)**

· **DOT**



· **Class**

3 Flammable liquids

· **Label**

3, 6.1

· **ADR**



· **Class**

3 (FT1) Flammable liquids

· **Label**

3+6.1

· **IMDG**



· **Class**

3 Flammable liquids

· **Label**

3/6.1

· **IATA**



· **Class**

3 Flammable liquids

· **Label**

3 (6.1)

· **Packing group**

II

· **DOT, ADR, IMDG, IATA**

· **Environmental hazards:**

Product contains environmentally hazardous substances: trilead bis(orthophosphate)

· **Special marking (ADR):**

Symbol (fish and tree)

· **Special precautions for user**

Warning: Flammable liquids

· **Danger code (Kemler):**

336

· **EMS Number:**

F-E,S-D

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

- **Transport in bulk according to Annex II of MARPOL73/II8 and the /BC Code** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations** On passenger aircraft: 1 L
On cargo aircraft only: 60 L
- **ADR**
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
- **UN Model Regulation:** UN1992, Flammable liquids, toxic, n.o.s. (Ethyl methyl ketone, Antimony trioxide), ENVIRONMENTALLY HAZARDOUS, 3 (6.1), II

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 Toluene
108-10-1 Methyl isobutyl ketone
1309-64-4 Antimony trioxide
7446-27-7 trilead bis(orthophosphate)
71-36-3 Butanol

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **California Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1 Methyl isobutyl ketone
1309-64-4 Antimony trioxide
7446-27-7 trilead bis(orthophosphate)

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3 | Toluene

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 | Toluene
108-10-1 Methyl isobutyl ketone

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

· **Carcinogenic categories**

| · EPA (Environmental Protection Agency) | |
|---|----|
| 108-88-3 Toluene | II |
| 108-10-1 Methyl isobutyl ketone | I |
| 7446-27-7 trilead bis(orthophosphate) | B2 |
| 71-36-3 Butanol | D |
| · TLV (Threshold Limit Value established by ACGIH) | |
| 108-88-3 Toluene | A4 |
| 1309-64-4 Antimony trioxide | A2 |
| 7446-27-7 trilead bis(orthophosphate) | A3 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08 GHS09

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Molybdenum Disulphide
Toluene
Methyl isobutyl ketone
trilead bis(orthophosphate)
Antimony trioxide

· **Hazard statements**

Flammable liquid and vapor.
Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
May damage fertility or the unborn child.
May cause respiratory irritation. May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Do not breathe dust/fume/gas/mist/vapors/spray.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves / eye protection / face protection.
Wear protective gloves.
Wear eye protection / face protection.
Ground/bond container and receiving equipment.

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

Use only non-sparking tools.
 Avoid release to the environment.
 Take precautionary measures against static discharge.
 Wash thoroughly after handling.
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 If swallowed: Immediately call a poison center/doctor.
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Call a poison center/doctor if you feel unwell.
 IF exposed or concerned: Get medical advice/attention.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.
 Do NOT induce vomiting.
 In case of fire: Use for extinction: CO2, powder or water spray.
 If on skin: Wash with plenty of water.
 Collect spillage.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

National regulations:

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

State Right to Know

| | | |
|-------------------------------------|--|--------|
| CAS: 108-88-3 RTECS: XS 5250000 | Toluene ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 | 15-35% |
| CAS: 1317-33-5 RTECS: QA 4697000 | Molybdenum Disulphide ⚠ Acute Tox. 4, H332 | 15-35% |
| CAS: 108-10-1 RTECS: SA 9275000 | Methyl isobutyl ketone ⚠ Flam. Liq. 2, H225; ⚠ Care. 2, H351; ⚠ Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335 | 15-35% |
| CAS: 78-93-3 RTECS: EL 6475000 | Methyl ethyl ketone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2A, H319; STOT SE 3, H336 | 15-35% |
| CAS: 28470-78-2 | Formaldehyde Polymer with 3-Chloro-1-Propene & Phenol ⚠ Skin Irrit. 2, H315; STOT SE 3, H335; Eye Irrit. 2B, H320 | 15-35% |
| CAS: 1309-64-4 | Antimony trioxide ⚠ Care. 2, H351 | 2-12% |

All ingredients are listed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of

(Contd. on page 15)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 06/15/2015

Reviewed on 03/17/2022

Trade name: Surf-Kote M-2049

this information and the suitability of the material or product for any particular purpose.

· **Date of preparation / last revision** 06/15/2015 / -

· **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road

AON: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

GAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 1A: Reproductive toxicity, Hazard Category 1A

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106